

Street Triple R Additional Information

STREET TRIPLE R ADDITIONAL INFORMATION

Part Number: 3852802 06/08

TRIUMPH

1 of 4

Street Triple R Additional Information


Street Triple R

This handbook addendum contains information for the ignition key, suspension, brakes, tyres and specifications for the Street Triple R and must be read in conjunction with the accompanying owner's handbook.

All other details are as described for the Street Triple in the accompanying owner's handbook.

Always keep this addendum with the owner's handbook, store them with the motorcycle and refer to them whenever necessary.

Ignition Key



ceom

1. Key number tag
2. Third key for alarm system

For Street Triple R there is a third key that does not have a fob. This is for the accessory alarm system.

Suspension Settings - Street Triple R Only

Warning

Ensure that the correct balance between front and rear suspension is maintained. Suspension imbalance could significantly change handling characteristics leading to loss of control and an accident. Refer to the chart below for further information or consult your dealer.

Warning

Ensure that the adjusters are set to the same settings on both forks. Settings which vary from left to right could significantly change handling characteristics leading to loss of control and an accident.

The standard suspension settings provide a comfortable ride and good handling characteristics for general, solo riding. The sport suspension settings provide sport-oriented handling characteristics with a slight sacrifice to rider comfort. The chart on the next page shows suggested settings for the front and rear suspension.

Note:

- **The suspension setting chart is only a guide for the Street Triple R, not any other model.**
- **Setting requirements may vary for rider weight and personal preferences.**

Street Triple R Additional Information

Suspension Setting Chart

LOADING		FRONT			REAR	
		Spring Pre-Load ¹	Rebound Damping ²	Compression Damping ²	Rebound Damping ²	Compression Damping ²
Solo Riding	Standard	7	4	4	8	8
	Softer	7	6	6	10	10
	Sport	7	2	2	6	6
Rider and Passenger		7	4	4	8	4
¹ Number of turns out from the fully screwed in position. ² Number of clicks out from the fully screwed in position.						

The method to adjust the front and rear suspension is the same as described for the Daytona 675 in the accompanying handbook, with the exception of the following:

- Front and rear suspension rebound damping - count the number of clicks out from the fully screwed in position;
- Front and rear suspension compression damping - count the number of clicks out from the fully screwed in position.

Note:

- **The motorcycle is delivered from the factory with the suspension set at the standard settings, as shown in the table above.**

Warning

The rear suspension unit spring pre-load is not rider adjustable. Any attempt to adjust the spring pre-load could result in a dangerous riding condition leading to loss of control and an accident.

Brakes

Brake Fluid Level Inspection and Adjustment

The inspection and adjustment of the brake fluid level in the reservoirs is the same as the Daytona 675. Refer to the Maintenance section in the accompanying handbook.

Street Triple R Additional Information

Tyre Options

Option	Front	Rear	Front Size	Rear Size
1	Dunlop Sportmax Qualifier	Dunlop Sportmax Qualifier	120/70 ZR 17	180/55 ZR 17
2	Bridgestone BT015 G	Bridgestone BT015 E		

Warning

Use the recommended tyre options ONLY in the combinations given. Do not mix tyres from different manufacturers or mix different specification tyres from the same manufacturers as this may result in loss motorcycle control and an accident.

Tyre Pressures

Front	2.35 Bar (34 lb/in ²)
Rear	2.90 Bar (42 lb/in ²)

Warning

Incorrect tyre inflation will cause abnormal tread wear and instability problems that may lead to loss of control and an accident. Under-inflation may result in the tyre slipping on, or coming off the rim. Over inflation will cause instability and accelerated tread wear. Both conditions are dangerous as they may cause loss of control leading to an accident.

Specifications

The specifications for the Street Triple R are the same as the Street Triple details given in the accompanying handbook with the exception of the following listed below.

Dimensions

Overall Length . . .	2,030 mm (79.9 in)
Overall Width . . .	755 mm (29.7 in)
Overall Height . . .	1,185 mm (46.7 in)
Wheelbase	1,385 mm (54.5 in)
Seat Height	805 mm (31.7 in)

Frame

Rake	23.9°
Trail	92.4 mm (3.64 in)